



66893

Pullulan (Polymaltotriose, PULL) extrapure

Part B

CAS : 9057-02-7

Specifications

Appearance (Colour)	White to off-white
Appearance (Form)	Powder
Loss on drying	max. 8%

Other Information

Application

Pullulan (PULL), a glucan polymer composed of $\alpha(1,6)$ linked maltotriose (three glucose) units, is used for the development of copolymers, permeability barrier coatings, nanofibers, nanospheres, nanogels, and biofilms with potential uses that range from protective food wrapping materials to biocompatible tissue engineering and drug delivery materials and structures.

General Information

Storage	8 to 25°C (Cool & Dry Area)
Shelf Life	60 Months
IMDG Identification	Not Regulated for Transport (Non-Haz)
HSN Code	
100 Gms	29400000 (GST 18%)
25 Gms	29400000 (GST 18%)
5 Gms	29400000 (GST 18%)
Type of Packing	
25 Gms	Glass Bottle

Available Packages

5 Gms

25 Gms

Disclaimer

The information represented here may/may not represent the entire product specification, application or protocol recommended by Sisco Research Laboratories Pvt. Ltd. (SRL). This information is for the user scientists or trading community as a guide in their applications. The company claims no liability for misuse resulting due to wrong usage of the information above. For actual batch related documents, mail us.

608-B, Satellite Gazebo, Andheri Ghatkopar Link Road, Chakala, Andheri (E), Mumbai - 400 099, Maharashtra, India. Telephone: +91-22-4268 5800, Email: info@srchem.com, website www.srchem.com