



92118

## Bentonite pure

Part A

CAS : 1302-78-9

### Specifications

Appearance (Colour)	Cream coloured
Appearance (Form)	Powder
pH	9.0 - 10.5
Loss on drying	max. 15%
Coarse particle	min. 0.5%
Heavy metals	max. 0.005%
Sedimentation volume	Passes
Swelling power	Passes

### Other Information

Notes

Bentonite is an absorbent aluminium phyllosilicate, impure clay consisting mostly of montmorillonite. The main uses of bentonite are for drilling mud, binder (e.g. foundry-sand bond, iron ore pelletizer), purifier, absorbent (e.g. pet litter), and as a groundwater barrier.

### General Information

Storage	25 to 40°C (Room Temperature)
Shelf Life	60 Months
IMDG Identification	Not Regulated for Transport (Non-Haz)
HSN Code	
5 Kg	25081010 (GST 5%)
500 Gms	25081010 (GST 5%)
Type of Packing	
500 Gms	Plastic Bottle

### Available Packages

500 Gms

#### Disclaimer

The information represented here may/may not represent the entire product specification, application or protocol recommended by Sisco Research Laboratories Pvt. Ltd. (SRL). This information is for the user scientists or trading community as a guide in their applications. The company claims no liability for misuse resulting due to wrong usage of the information above. For actual batch related documents, mail us.

608-B, Satellite Gazebo, Andheri Ghatkopar Link Road, Chakala, Andheri (E), Mumbai - 400 099, Maharashtra, India. Telephone: +91-22-4268 5800, Email: info@srchem.com, website www.srchem.com